

AMENDMENTS TO THE CLAIMS

This listing of claims will replace all prior versions, and listings, of claims in the application:

1. (currently amended) A method for controlling access to a resource, the method comprising the steps of:

creating and storing in a filesystem of an Operating System a file that represents the resource;

receiving user-identifying information from a user requesting access to the resource, wherein the user-identifying information comprises a role associated with the user, wherein the role is determined from a user identifier uniquely associated with the user and from a group identifier associated with a group that includes the user;

receiving a resource identifier associated with the resource;

creating an access identifier based on the user-identifying information and the resource identifier, wherein the access identifier is formatted as a file attribute that is used by the Operating System to manage file access;

calling the Operating System to perform a file operation on the file by providing the access identifier to the ~~Operation~~ Operating System to attempt access to the file;

and

granting the user access to the resource when the Operating System call successfully performs the file operation;

wherein the file operation on the file representing the resource is selected from a group consisting of opening the file, closing the file, deleting the file, reading from the file, writing to the file, executing the file, appending to the file, reading a file attribute, and writing a file attribute.

2. (original) A method as recited in Claim 1, wherein the access identifier comprises:
a first set of bits for storing a role identifier, wherein the role identifier is associated with
the role; and
a second set of bits for storing the resource identifier.
3. (original) A method as recited in Claim 1, wherein:
the step of creating an access identifier based on the user-identifying information and the
resource identifier comprises formatting the access identifier as a group identifier
file attribute; and
the step of calling the Operating System to perform an operation on the file representing
the resource comprises:
assigning the access identifier to a group identifier attribute of an
Operating System process; and
calling an Operating System routine from the Operating System process to
perform the operation on the file representing the resource.
4. (original) A method as recited in Claim 1, wherein the step of calling the Operating
System to perform an operation on the file representing the resource comprises
comparing the access identifier to an identifier included in an Access Control List file
attribute associated with the file representing the resource, wherein the Access Control
List file attribute includes the identifiers of all users and all groups of users allowed to
access the file representing the resource.
5. (cancelled).

6. (previously presented) A method as recited in Claim 1, the method further comprising the steps of:

reading a permission bit associated with the file representing the resource, wherein the

permission bit corresponds to the operation performable on the file representing

the resource;

based on the operation on the file indicated by the permission bit, determining a resource

operation that is performable on the resource; and

granting the user the privilege of performing the resource operation on the resource only

if the permission bit allows the operation to be performed on the file representing

the resource.
7. (original) A method as recited in Claim 1, the method further comprising the steps of:

opening the file representing the resource;

reading from the file representing the resource a permission indicator associated with a

resource operation; and

enabling the user to perform the resource operation on the resource only if the permission

indicator indicates that the user is allowed to perform the resource operation on

the resource.
8. (original) A method as recited in Claim 1, wherein the step of representing the resource

by a file stored in the Operating System filesystem comprises:

creating the file representing the resource in the Operating System filesystem; and

assigning an access value to a file attribute of the file representing the resource, the file attribute being used by the Operating System to manage file access, wherein the access value corresponds to a combination of a role and a resource.

9. (original) A method as recited in Claim 8, wherein the file attribute used by the Operating System to manage file access is a group identifier file attribute.

10. (previously presented) A method for controlling access to a resource, the method comprising the steps of:
receiving a user identifier from a user requesting access to the resource, wherein the user identifier is uniquely associated with the user;
receiving a group identifier associated with a group to which the user belongs;
based on the user identifier and the group identifier, determining a role associated with the user, wherein a role identifier is uniquely associated with the role;
receiving a resource identifier associated with the resource, wherein the resource is represented by a file stored in a filesystem of an Operating System;
constructing an access identifier on the basis of the role identifier and the resource identifier, wherein the access identifier conforms to the format of a group identifier file attribute that is used by the Operating System to manage file access;
making an Operating System call to perform a file operation on the file representing the resource, wherein the Operating System call uses the access identifier to gain access to the file representing the resource; and
granting the user access to the resource when the Operating System call successfully performs the file operation on the file representing the resource;

wherein the file operation on the file representing the resource is selected from a group consisting of opening the file, closing the file, deleting the file, reading from the file, writing to the file, executing the file, appending to the file, reading a file attribute, and writing a file attribute.

11. (original) A method as recited in Claim 10, wherein the access identifier comprises:
a first set of bits for storing the role identifier, wherein the role identifier represents a bitmap, each bit of the bitmap uniquely associated with a role of the user; and
a second set of bits for storing the resource identifier.
12. (original) A method as recited in Claim 10, wherein the step of making an Operating System call to perform an operation on the file representing the resource comprises:
storing the group identifier value of a group identifier attribute of an Operating System process;
assigning the access identifier to the group identifier attribute of the Operating System process;
calling an Operating System routine from the Operating System process to perform the operation on the file representing the resource, wherein the operation on the file representing the resource is performed only if the value of the group identifier attribute of the Operating System process matches the value of the group identifier file attribute of the file representing the resource; and
resetting the group identifier attribute of the Operating System process to the stored group identifier value.

13. (original) A method as recited in Claim 10, wherein the step of making an Operating System call to perform an operation on the file representing the resource comprises comparing the access identifier to an identifier included in an Access Control List file attribute associated with the file representing the resource, wherein the Access Control List file attribute includes the identifiers of all users and all groups of users allowed to access the file representing the resource.
14. (cancelled).
15. (original) A method as recited in Claim 10, the method further comprising the steps of:
reading a permission bit associated with the file representing the resource, wherein the
permission bit corresponds to a file operation performable on the file representing
the resource;
based on the file operation indicated by the permission bit, determining a resource
operation that is performable on the resource; and
granting the user the privilege of performing the resource operation on the resource only
if the permission bit allows the file operation to be performed on the file
representing the resource.
16. (original) A method as recited in Claim 10, the method further comprising the steps of:
opening the file representing the resource;
reading from the file representing the resource a permission indicator associated with a
resource operation; and

granting the user the privilege of performing the resource operation on the resource only
if the permission indicator indicates that the user is allowed to perform the
resource operation on the resource.

17. (original) A method as recited in Claim 10, the method further comprising:
creating the file representing the resource in the Operating System filesystem; and
assigning an access value to a group identifier file attribute of the file representing the
resource, the group identifier file attribute being used by the Operating System to
manage file access, wherein the access value is uniquely determined by the
combination of a role and a resource.
18. (previously presented) A system for controlling access to a resource connected to a
network, the system comprising:
a client host capable of accessing the resource in response to a request for access from a
user;
one or more processors executing an Operating System, wherein the Operating System
operatively controls a filesystem that includes a number of files; and
a computer readable medium having stored therein an Application Programming
Interface, wherein the Application Programming Interface is logically interposed
between the client host and the Operating System and comprises one or more
routines including routines which, when executed by the one or more processors,
cause the one or more processors to perform the steps of:
creating and storing in the filesystem a file that represents the resource;

receiving user-identifying information from the user requesting access to the resource, wherein the user-identifying information comprises a role associated with the user, wherein the role is determined from a user identifier uniquely associated with the user and from a group identifier associated with a group that includes the user;

receiving a resource identifier associated with the resource;

creating an access identifier based on the user-identifying information and the resource identifier, wherein the access identifier is formatted as a file attribute that is used by the Operating System to manage file access;

calling the Operating System to perform a file operation on the file by providing the access identifier to the Operating System to attempt access to the file;

and

granting the user access to the resource when the Operating System call successfully performs the file operation;

wherein the file operation on the file representing the resource is selected from a group consisting of opening the file, closing the file, deleting the file, reading from the file, writing to the file, executing the file, appending to the file, reading a file attribute, and writing a file attribute.

19. (original) A system as recited in Claim 18, wherein the access identifier comprises:
- a first set of bits for storing a role identifier, wherein the role identifier is associated with the role; and
- a second set of bits for storing the resource identifier.

20. (original) A system as recited in Claim 18, wherein:

the step of creating an access identifier based on the user-identifying information and the resource identifier comprises formatting the access identifier as a group identifier file attribute; and

the step of calling the Operating System to perform an operation on the file representing the resource comprises:

assigning the access identifier to a group identifier attribute of an

Operating System process; and

calling an Operating System routine from the Operating System process to perform the operation on the file representing the resource.

21-38 (canceled)

39. (previously presented) A computer-readable medium, for controlling access to a resource, carrying one or more sequences of instructions which, when executed by one or more processors, causes the one or more processors to perform the steps of:

creating and storing in a filesystem of an Operating System a file that represents the resource;

receiving user-identifying information from a user requesting access to the resource,

wherein the user-identifying information comprises a role associated with the

user, wherein the role is determined from a user identifier uniquely associated

with the user and from a group identifier associated with a group that includes the

user;

receiving a resource identifier associated with the resource;

creating an access identifier based on the user-identifying information and the resource identifier, wherein the access identifier is formatted as a file attribute that is used by the Operating System to manage file access;

calling the Operating System to perform a file operation on the file by providing the access identifier to the Operating System to attempt access to the file; and

granting the user access to the resource when the Operating System call successfully performs the file operation;

wherein the file operation on the file representing the resource is selected from a group consisting of opening the file, closing the file, deleting the file, reading from the file, writing to the file, executing the file, appending to the file, reading a file attribute, and writing a file attribute.

40. (previously presented) A computer-readable medium as recited in Claim 39, wherein the access identifier comprises:
- a first set of bits for storing a role identifier, wherein the role identifier is associated with the role; and
- a second set of bits for storing the resource identifier.
41. (previously presented) A computer-readable medium as recited in Claim 39, wherein:
- the step of creating an access identifier based on the user-identifying information and the resource identifier comprises formatting the access identifier as a group identifier file attribute; and
- the step of calling the Operating System to perform an operation on the file representing the resource comprises:

assigning the access identifier to a group identifier attribute of an

Operating System process; and

calling an Operating System routine from the Operating System process to

perform the operation on the file representing the resource.

42. (previously presented) A computer-readable medium as recited in Claim 39, wherein the step of calling the Operating System to perform an operation on the file representing the resource comprises comparing the access identifier to an identifier included in an Access Control List file attribute associated with the file representing the resource, wherein the Access Control List file attribute includes the identifiers of all users and all groups of users allowed to access the file representing the resource.

43. (cancelled)

44. (previously presented) A computer-readable medium as recited in Claim 39, carrying one or more additional sequences of instructions which, when executed by one or more processors, further causes the one or more processors to perform the steps of:

reading a permission bit associated with the file representing the resource, wherein the

permission bit corresponds to a file operation performable on the file representing the resource;

based on the file operation indicated by the permission bit, determining a resource

operation that is performable on the resource; and

granting the user the privilege of performing the resource operation on the resource only
if the permission bit allows the file operation to be performed on the file
representing the resource.

45. (previously presented) A computer-readable medium as recited in Claim 39, carrying one or more additional sequences of instructions which, when executed by one or more processors, further causes the one or more processors to perform the steps of:
opening the file representing the resource;
reading from the file representing the resource a permission indicator associated with a resource operation; and
enabling the user to perform the resource operation on the resource only if the permission indicator indicates that the user is allowed to perform the resource operation on the resource.
46. (previously presented) A computer-readable medium as recited in Claim 39, wherein the step of representing the resource by a file stored in the Operating System filesystem comprises:
creating the file representing the resource in the Operating System filesystem; and
assigning an access value to a file attribute of the file representing the resource, the file attribute being used by the Operating System to manage file access, wherein the access value corresponds to a combination of a role and a resource.

47. (previously presented) A computer-readable medium as recited in Claim 46, wherein the file attribute used by the Operating System to manage file access is a group identifier file attribute.
48. (previously presented) A computer-readable medium, for controlling access to a resource, carrying one or more sequences of instructions which, when executed by one or more processors, causes the one or more processors to perform the steps of:
- receiving a user identifier from a user requesting access to the resource, wherein the user identifier is uniquely associated with the user;
- receiving a group identifier associated with a group to which the user belongs;
- based on the user identifier and the group identifier, determining a role associated with the user, wherein a role identifier is uniquely associated with the role;
- receiving a resource identifier associated with the resource, wherein the resource is represented by a file stored in a filesystem of an Operating System;
- constructing an access identifier on the basis of the role identifier and the resource identifier, wherein the access identifier conforms to the format of a group identifier file attribute that is used by the Operating System to manage file access;
- making an Operating System call to perform a file operation on the file representing the resource, wherein the Operating System call uses the access identifier to gain access to the file representing the resource; and
- granting the user access to the resource when the Operating System call successfully performs the file operation on the file representing the resource;
- wherein the file operation on the file representing the resource is selected from a group consisting of opening the file, closing the file, deleting the file, reading from the

file, writing to the file, executing the file, appending to the file, reading a file attribute, and writing a file attribute.

49. (previously presented) A computer-readable medium as recited in Claim 48, wherein the access identifier comprises:
- a first set of bits for storing the role identifier, wherein the role identifier represents a bitmap, each bit of the bitmap uniquely associated with a role of the user; and
- a second set of bits for storing the resource identifier.
50. (previously presented) A computer-readable medium as recited in Claim 48, wherein the step of making an Operating System call to perform an operation on the file representing the resource comprises:
- storing the group identifier value of a group identifier attribute of an Operating System process;
- assigning the access identifier to the group identifier attribute of the Operating System process;
- calling an Operating System routine from the Operating System process to perform the operation on the file representing the resource, wherein the operation on the file representing the resource is performed only if the value of the group identifier attribute of the Operating System process matches the value of the group identifier file attribute of the file representing the resource; and
- resetting the group identifier attribute of the Operating System process to the stored group identifier value.

51. (previously presented) A computer-readable medium as recited in Claim 48, wherein the step of making an Operating System call to perform an operation on the file representing the resource comprises comparing the access identifier to an identifier included in an Access Control List file attribute associated with the file representing the resource, wherein the Access Control List file attribute includes the identifiers of all users and all groups of users allowed to access the file representing the resource.
52. (cancelled)
53. (previously presented) A computer-readable medium as recited in Claim 48, carrying one or more additional sequences of instructions which, when executed by one or more processors, further causes the one or more processors to perform the steps of:
reading a permission bit associated with the file representing the resource, wherein the
permission bit corresponds to a file operation performable on the file representing
the resource;
based on the file operation indicated by the permission bit, determining a resource
operation that is performable on the resource; and
granting the user the privilege of performing the resource operation on the resource only
if the permission bit allows the file operation to be performed on the file
representing the resource.
54. (previously presented) A computer-readable medium as recited in Claim 48, carrying one or more additional sequences of instructions which, when executed by one or more processors, further causes the one or more processors to perform the steps of:

- opening the file representing the resource;
- reading from the file representing the resource a permission indicator associated with a resource operation; and
- granting the user the privilege of performing the resource operation on the resource only if the permission indicator indicates that the user is allowed to perform the resource operation on the resource.
55. (previously presented) A computer-readable medium as recited in Claim 48, carrying one or more additional sequences of instructions which, when executed by one or more processors, further causes the one or more processors to perform the steps of:
- creating the file representing the resource in the Operating System filesystem; and
- assigning an access value to a group identifier file attribute of the file representing the resource, the group identifier file attribute being used by the Operating System to manage file access, wherein the access value is uniquely determined by the combination of a role and a resource.
56. (previously presented) An apparatus for controlling access to a resource, comprising:
- means for creating and storing in an Operating System filesystem a file that represents the resource;
- means for receiving user-identifying information from a user requesting access to the resource, wherein the user-identifying information comprises a role associated with the user, wherein the role is determined from a user identifier uniquely associated with the user and from a group identifier associated with a group that includes the user;

means for receiving a resource identifier associated with the resource;

means for creating an access identifier based on the user-identifying information and the resource identifier, wherein the access identifier is formatted as a file attribute that is used by the Operating System to manage file access;

means for calling the Operating System to perform a file operation on the file by providing the access identifier to the Operating System to attempt access to the file; and

means for granting the user access to the resource when the Operating System call successfully performs the file operation;

wherein the file operation on the file representing the resource is selected from a group consisting of opening the file, closing the file, deleting the file, reading from the file, writing to the file, executing the file, appending to the file, reading a file attribute, and writing a file attribute.

57. (previously presented) An apparatus as recited in Claim 56, wherein the access identifier comprises:

a first set of bits for storing a role identifier, wherein the role identifier is associated with the role; and

a second set of bits for storing the resource identifier.

58. (previously presented) An apparatus as recited in Claim 56, wherein:

means for creating an access identifier based on the user-identifying information and the resource identifier comprises means for formatting the access identifier as a group identifier file attribute; and

means for calling the Operating System to perform an operation on the file representing

the resource comprises:

means for assigning the access identifier to a group identifier attribute of
an Operating System process; and

means for calling an Operating System routine from the Operating System
process to perform the operation on the file representing the
resource.

59. (cancelled)